AUTOMATIC BELL DRINKERS

RIVER

riversystems.



Automatic bell drinkers are suitable to chickens, laying hens, geese and turkeys. They are equipped with an automatic valve that regulates the water level.

They are supplied complete with a suspension cord, adjusting eyelets and hose guide, hose connector for 12x17 mm and 6x9 mm hoses and assembly instructions.

The drinkers are made of high-quality plastic and are easy to clean. Ideal for hobby and professional use.

The drinkers are designed to be used with a water pressure of 0.2-0.5 bar (recommended 0.3 bar). The optimum water level in the trough is between 10 and 20 mm.



Internal valve (art. 1050)

An essential component of our 1070, 1080 and 1090 valves. Each valve is 100% manufactured and tested in our factories.

PRODUCT DETAILS



(1)Inline valve (art.1070)

The body of the valve has been renewed and made more ergonomic. The valve is equipped with a hose connection suitable for use with 12x17 mm and 6x9 mm hoses. It mounted on art. 8060 and 8030.

Side valve (art.1080) Suitable for use on art. 8040. Side valve (art.1090) Suitable for use on art. 8050.

Water level adjustment

- Possibility to adjust the water level in the water trough;
- Recommended pre-loading distance spring: 24 mm approx. for Art. 8060
- 27 mm approx. for Art. 8030 56 mm approx. for Art. 8040 53 mm approx. for Art. 8050
- Increase the distance between the rings (Art. 8060 and 8030)/ ring and rod end (Art. 8050 and 8040), to decrease the maximum water level in the water trough.



Adjustment eyelet and hose guide

New ergonomically designed eyelet adjustment system that makes height adjustment quick and easy.





www.riversystems.it via Marco Polo 33, 35011 Campodarsego (PD) Italia Telefono: (+39) 0499202464 Email: info@riversystems.it





DNV



AUTOMATIC BELL DRINKERS









AUTOMATIC BELL DRINKERS